

Product data sheet ST 220



Service terminal for the wireless and wired parameter setting of GEZE door and window products

AREAS OF APPLICATION

- → Emergency exit system door control units
- → Motor locks
- ightarrow Building automation components
- → Automatic door drives
- → Automatic window drives

ST 220



PRODUCT FEATURES

- → Four-line display and slim user interface for simple operation
- → IR interface for the wireless parameter setting of emergency exit system door control units
- → Wired parameter setting via RS 485 bus
- \rightarrow Voltage supply via cable in the case of wired operation
- ightarrow 4x AAA batteries required for IR interface

TECHNICAL DATA

Productname	ST 220		
Width	80 mm		
Height	125 mm		
Depth	37 mm		
IP rating	IP40		
Operating voltage	24 V		
protection rating III			

VARIANTS / ORDER INFO

Designation	Description	Ident- No.	Colour	Dimensions	Operating voltage
ST 220 service terminal	For parameter setting and diagnosis for TZ 320, TE 220, automatic door systems, drives from the IQ windowdrive series and THZ N4, THZ Comfort N4, battery operation with 4x AAA cells (not supplied by GEZE), plain text display on illuminated panel, keypad for operation / Parameter changes to GEZE systems may only be carried out by experts who have been authorised by the manufacturer	087261	blue	80 x 125 x 37 mm	24 V