

Product data sheet

ISM guide rail TS 5000

extra length



Up to 3200 mm with closing sequence control and levers

AREAS OF APPLICATION

- Double leaf doors with closing sequence control
- Installation on hinge side
- Right and left single-action doors
- Symmetrical and asymmetrical division of door possible
- Up to 3200 mm hinge clearance
- Minimum hinge clearance 1300 mm, minimum width of passive leaf 400 mm

ISM guide rail TS 5000 extra length



PRODUCT FEATURES

- Closing sequence control holds the active leaf in the waiting position until the passive leaf is closed
- Vandalism protection through flexible Bowden cable
- Horizontally adjustable in the installation position by 4 mm through elongated holes
- With screwed slide block

TECHNICAL DATA

Productname	ISM guide rail TS 5000 extra length
Minimum hinge clearance	1300 mm
Minimum passive leaf width	400 mm
Standard conformity	EN 1158
Length	3030 mm
Width	40 mm
Height	30 mm
opening restrictor upgradable	Yes
Smoke switch integrated	No
Closing sequence control integrated	Yes
Height correction possible	Yes
Flexible opening restrictor	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Dimensions
ISM guide rail TS 5000 extra length	continuous, overlength up to 3200 mm, with integrated closing sequence control and levers	115598	silver-coloured	3030 x 40 x 30 mm
ISM guide rail TS 5000 extra length	continuous, overlength up to 3200 mm, with integrated closing sequence control and levers	115599	according to RAL	3030 x 40 x 30 mm

ISM guide rail TS 5000 extra length



ACCESSORIES

MECHANICAL HOLD-OPEN UNIT

For ISM guide rail



Designation	Description	Ident-No.
Mechanical hold-open unit	for ISM-guide rail / ISM-guide rail BG, retention force adjustable, can be overridden	118437

FLEXIBLE OPENING RESTRICTOR

For E and R guide rails, single and double leaf



Designation	Description	Ident-No.
Flexible opening restrictor	for guide rail 1-leaf: TS 5000 E/R/RFS (door leaf installation), Boxer E; 2-leaf: all E/R/ISM variants TS 5000 (incl. VPK) and Boxer	145311

KIT ECLINE ISM / ISM BG *

Power storage for use on the active leaf in double leaf ISM and ISM BG guide rails



Designation	Description	Ident-No.	Colour
Kit Ecline ISM / ISM BG *	Power storage for use on the active leaf in double leaf ISM and ISM BG guide rails	154767	black

ISM guide rail TS 5000 extra length



INSTALLATION MATERIAL

MOUNTING PLATE GUIDE RAIL

For ISM and E-ISM guide rail



Designation	Description	Ident-No.	Colour
Mounting plate guide rail	for ISM / E-ISM guide rail	118702	silver-coloured
Mounting plate guide rail	for ISM / E-ISM guide rail	118703	according to RAL

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.