

Product data sheet

Closer body TS 1000 C

*



Basic body for overhead door closer with link arm EN 2/3

AREAS OF APPLICATION

- Right and left single-action doors for interior use
- Single-action doors up to 950 mm leaf width
- Door leaf installation hinge side and transom installation opposite hinge side
- Door leaf installation opposite hinge side in parallel arm installation possible

Closer body TS 1000 C *



PRODUCT FEATURES

- Two different variable closing force settings, which can be selected simply by turning the bearing block for the link arm
- Closing speed can be adjusted from the side via valve
- Latching action can be adjusted from the side via valve
- Door closer, can be used for right and left hand doors

TECHNICAL DATA

| | |
|---|---|
| Productname | Closer body TS 1000 C * |
| Closing force in accordance with EN 1154 | EN 2/3 |
| Leaf width (max.) | 950 mm |
| Type of installation | Door leaf installation hinge side, Transom installation opposite hinge side, Door leaf installation opposite hinge side |
| Opening angle (max.) | 180 ° |
| Identical design for DIN left and DIN right | Yes |
| Standard conformity | EN 1154:1996/A1:2002/AC:2006 |
| Suitability for fire protection doors | Yes |
| Length | 215 mm |
| Width | 44 mm |
| Height | 52 mm |
| Closing force adjustable | Yes, via installation |
| Adjustable closing speed | Yes |
| Latching action adjustable | Yes, via valve |
| Back check integrated | No |
| Position of closing force adjustment | Mounting position |
| Smoke switch integrated | No |

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.