

Product data sheet TS 3000 EC *



Overhead door closer with guide rail for single leaf doors up to 950 mm leaf width

AREAS OF APPLICATION

- → Fire and smoke protection doors
- → Right and left single-action doors
- → Single-action doors up to 950 mm leaf width
- ightarrow Door leaf and transom installation on the hinge and opposite hinge side



PRODUCT FEATURES

- ightarrow Door closer with guide rail and closing force EN2-3 adjustable at the side
- → Can be used for right and left hand doors without conversion
- → Hydraulic latching action which accelerates the door shortly before it is closed
- ightarrow Closing speed can be individually adjusted
- ightarrow All functions can be set from the front (except for closing force)

TECHNICAL DATA

Productname	TS 3000 EC *
Closing force in accordance with EN 1154	EN 2 - 3
Barrier-free in accordance with DIN 18040 up to leaf width (max.) in mm	950 mm
Leaf width (max.)	950 mm
Type of installation	Door leaf installation hinge side, Transom installation opposite hinge side, Transom installation hinge side, Door leaf installation opposite hinge side
Opening angle (max.)	180°
Suitability for fire protection doors	Yes
Closing force adjustable	Yes, stepless
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Back check integrated	No
Position of closing force adjustment	At the side
Hold-open function	Optional
Smoke switch integrated	No

PART

GUIDE RAIL TS 5000 / 3000 VERTICALLY ADJUSTABLE *

With height compensation +/- 2 mm and lever



GEZE GmbH Reinhold-Vöster-Straße 21–29 D-71229 Leonberg TEL +49 7152 203-0 WEB www.geze.de Mail info.de@geze.com 2024-04-14T03:16:13Z



Designation	Description	Ident-No.	Colour	Dimensions
Guide rail TS 3/5000 vertically adjustable	Height compensation +/- 2 mm, with lever	115191	silver-coloured	448.5 x 30.5 x 20.5 mm
Guide rail TS 3/5000 vertically adjustable	Height compensation +/- 2 mm, with lever	115192	according to RAL	448.5 x 30.5 x 20.5 mm

GUIDE RAIL BG TS 5000 / 3000 VERTICALLY ADJUSTABLE *

With height compensation +/- 2 mm, with lever, opposite hinge side



Designation	Description	Ident- No.	Colour	Dimensions
Guide rail BG TS 3/5000 vertically adjustable	Height compensation +/- 2 mm, with lever, use with closer on leaf installation on the opposite hinge side	115194	according to RAL	448.5 x 30.5 x 20.5 mm
Guide rail BG TS 3/5000 vertically adjustable	Height compensation +/- 2 mm, with lever, use with closer on leaf installation on the opposite hinge side	115193	silver- coloured	448.5 x 30.5 x 20.5 mm

GUIDE RAIL TS 5000 / 3000

Standard guide rail with lever



Designation	Description	Ident-No.	Colour	Dimensions	Spindle extension
Guide rail TS 3/TS 5000	Standard, with lever	015695	white RAL 9016	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/TS 5000	Standard, with lever	000773	according to RAL	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/TS 5000	Standard, with lever	068221	silver-coloured	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/TS 5000	Standard, with lever	014945	Stainless steel optic	448.5 x 30.5 x 20.5 mm	



GUIDE RAIL BG TS 5000 / 3000

Standard guide rail with lever, opposite hinge side



Designation	Description	Ident-No.	Colour	Dimensions
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	025655	silver-coloured	448.5 x 30.5 x 20.5 mm
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	025656	according to RAL	448.5 x 30.5 x 20.5 mm
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	029404	white RAL 9016	448.5 x 30.5 x 20.5 mm
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	028732	Stainless steel optic	448.5 x 30.5 x 20.5 mm

TS 3000 EC *

Overhead door closer with guide rail for single leaf doors up to 950 mm leaf width



Designation	Description	Ident- No.	Colour	Closing force in accordance with EN 1154	Dimensions
GEZE TS 3000 EC closer *	Size EN 2-3 (without guide rail and lever)	126139	according to RAL	EN 2 - 3	226 x 46 x 60 mm
GEZE TS 3000 EC closer *	Size EN 2-3 (without guide rail and lever)	126137	dark bronze	EN 2 - 3	226 x 46 x 60 mm
GEZE TS 3000 EC closer *	Size EN 2-3 (without guide rail and lever)	126136	silver-coloured	EN 2 - 3	226 x 46 x 60 mm

T-STOP GUIDE RAIL BG TS 3000 / 5000

With opening restrictor and lever, opposite hinge side



GEZE GmbH | Reinhold-Vöster-Straße 21-29 | D-71229 Leonberg | TEL +49 7152 203-0 | WEB www.geze.de | Mail info.de@geze.com 2024-04-14T03:16:14Z



Designation	Description	ldent- No.	Colour	Dimensions
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102368	according to RAL	452.5 x 33 x 30 mm
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102367	Stainless steel optic	452.5 x 33 x 30 mm
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	108482	white RAL 9016	452.5 x 33 x 30 mm
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102366	silver-coloured	452.5 x 33 x 30 mm

T-STOP GUIDE RAIL TS 3000/5000

With opening restrictor and lever



Designation	Description	Ident-No.	Colour	Dimensions
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	108481	white RAL 9016	452.5 x 33 x 30 mm
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102364	Stainless steel optic	452.5 x 33 x 30 mm
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102365	according to RAL	452.5 x 33 x 30 mm
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102363	silver-coloured	452.5 x 33 x 30 mm

ACCESSORIES

COVER CAP DOOR CLOSER *

For TS 3000/TS 2000, curved shape

Designation	Description	Ident-No.	Colour	Dimensions
Cover cap door closer *	for TS 3000/TS 2000, semi-radial, can only be used for door leaf installation	092928	Polished stainless steel	277 x 54 x 72 mm
Cover cap door closer *	for TS 3000/TS 2000, semi-radial, can only be used for door leaf installation	092929	Satin stainless steel	277 x 54 x 72 mm

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | TEL +49 7152 203-0 | WEB www.geze.de | Mail info.de@geze.com



COVER CAP DOOR CLOSER *

For TS 3000/TS 2000, rectangular shape

Designation	Description	Ident-No.	Colour	Dimensions
Cover cap door closer *	for TS 3000 / TS 2000, square, can only be used for door leaf installation	092924	Satin stainless steel	237 x 54 x 72 mm
Cover cap door closer *	for TS 3000 / TS 2000, square, can only be used for door leaf installation	092923	Polished stainless steel	237 x 54 x 72 mm

COVER CAP DOOR CLOSER *

For TS 3000/TS 2000, can only be used for door leaf installation



Designation	Description	Ident-No.	Colour	Dimensions
Cover cap door closer	for TS 3000 / TS 2000, can only be used for door leaf installation	072769	Stainless steel	237 x 55 x 67.2 mm
Cover cap door closer	for TS 3000 / TS 2000, can only be used for door leaf installation	072770	Brass	237 x 55 x 67.2 mm
Cover cap door closer	for TS 3000 / TS 2000, can only be used for door leaf installation	013487	silver-coloured	237 x 55 x 67.2 mm
Cover cap door closer	for TS 3000 / TS 2000, can only be used for door leaf installation	014855	white RAL 9016	237 x 55 x 67.2 mm
Cover cap door closer	for TS 3000 / TS 2000, can only be used for door leaf installation	014849	dark bronze	237 x 55 x 67.2 mm
Cover cap door closer	for TS 3000 / TS 2000, can only be used for door leaf installation	014856	according to RAL	237 x 55 x 67.2 mm

MECHANICAL HOLD-OPEN UNIT

For standard/T-Stop/Boxer 20.7 mm guide rail



Designation	Description	Ident-No.
Mechanical hold-open unit	for standard / T-Stop / Boxer 20.7 mm guide rail, retention force adjustable, can be switched on and off, can be overridden	071924

GEZE GmbH | Reinhold-Vöster-Straße 21-29 | D-71229 Leonberg | TEL +49 7152 203-0 | WEB www.geze.de | Mail info.de@geze.com 2024-04-14T03:16:14Z



FLEXIBLE OPENING RESTRICTOR

for riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail



Designation	Description	Ident-No.
Flexible opening restrictor	for riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail	069780

^{*} The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.