

Product data sheet

GEZE ActiveStop

integrated



Door damper on both sides for interior wooden swing doors

AREAS OF APPLICATION

- Right and left timber single-action doors indoors
- Room doors with high access convenience
- Single-action doors up to 1100 mm leaf width
- Integrated installation in the door leaf
- Barrier-free access in accordance with DIN 18040-2

GEZE ActiveStop integrated



PRODUCT FEATURES

- Door opening angle with variable adjustment from 80°-140°
- Can be used for right and left hand doors without conversion
- Soft opening and closing of doors up to max. 45 kg leaf weight
- Gentle stopping, quiet closing and comfortable keeping open of doors
- Practically eliminates slamming doors, trapped fingers, and damage to walls and furniture
- Secure holding of the door when open, meaning no door is stopper necessary
- Opening and latching speed when installed can be set via a valve
- Integrated safety valve offers overload protection

TECHNICAL DATA

Productname	GEZE ActiveStop integrated
Depth	28 mm
Height	64 mm
Leaf weight (max.)	45 kg
Leaf width (max.)	1100 mm
Category of door	flush-mounted, rebated
Leaf thickness from	38 mm
Identical design for DIN left and DIN right	Yes
Rebate space	approx. 6 mm clearance in handle area
Installation type	concealed
Adjustable draw-in damper	Yes, via valve
Draw-in damper in direction of closing movement from	25 °
Free swing area	25 ° - 60 °
Draw-in damper in direction of opening movement from	60 °
Adjustable door opening angle	Yes, stepless
Hold-open position adjustable	80 ° - 140 °
Safety valve against overload	Yes

VARIANTS / ORDER INFO

Designation

GEZE ActiveStop integrated

ACCESSORIES

MILLING EDGE COVER *

For covering the milling edge of rebated doors



Designation

Milling edge cover *

Milling edge cover *

Milling edge cover

MILLING FIXTURE *

For milling door leaves and frames for the GEZE ActiveStop integrated



Designation

Milling fixture *

GUIDE RAIL FIXING PLATES

For fixing the concealed horizontally installed guide rail if there is insufficient screw depth



Designation

Fastening strips for guide rails

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.