

# Product data sheet UFO NT \*



Electromechanical floor-mounted swing door drive for single leaf doors weighing up to 125 kg

## **AREAS OF APPLICATION**

- ightarrow Single-action, single leaf, right and left closing doors
- ightarrow Doors up to 1100 mm leaf width or 125 kg in weight
- ightarrow Minimum door leaf width is 600 mm
- ightarrow Interior and exterior doors with high access frequency
- ightarrow Floor mounting, concealed



#### **PRODUCT FEATURES**

- ightarrow Drive unit is embedded in the floor and meets the highest design expectations
- ightarrow High degree of IP protection and sealed stainless steel housing for outdoor use
- ightarrow Smart swing function for easy manual door opening
- ightarrow Closing force with variable adjustment
- ightarrow Opening and closing speed can be individually adjusted
- → Mechanical latching action when operated without current, and electrical automatic unit latching action in regular operation, which accelerates the door shortly before it is closed
- ightarrow Low-energy function opens and closes the door with reduced speed, fulfilling the highest safety demands
- ightarrow Obstacle detection detects an object through contact and stops the opening or closing process
- ightarrow Push & Go function triggers the automatic drive following light manual pressure on the door leaf

### **TECHNICAL DATA**

| UFO NT *          |
|-------------------|
| 150 mm            |
| 195 mm            |
| 125 kg            |
| 1200 mm - 2200 mm |
| 600 mm - 1600 mm  |
| Electromechanical |
| 130 °             |
| Yes               |
| Yes               |
| Yes               |
| Yes, stepless     |
| EN 1 - 4          |
| 10 s              |
| 200 W             |
| 1200 mA           |
| -15 - 50 °C       |
| IP67              |
| Fully automatic   |
| Yes               |
| Yes               |
| Yes               |
| Yes               |
| No                |
|                   |



#### **VARIANTS / ORDER INFO**

| Designation | Ident-No. | Supply voltage | Closing force in accordance with EN 1154 | Dimensions         | Leaf width (min.) |
|-------------|-----------|----------------|--|--------------------|-------------------|
| UFO NT *    | 164823    | 230 V          | EN 1 - 4                                 | 490 x 195 x 150 mm | 600 mm            |

\* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.